SAFETY DATA SHEET

Emergency telephone number (24 hour)

Chemtrec (US and Canada): +1-800-424-9300



Date issued: 01/21/2015 SDS number: N-110 Date revised: 10/10/2023

Revision number: 7

1. Identification

Product code: N-110

Product description: Metering Roller Cleaner and Ultra-Fast-Dry Roller and Blanket Wash

Manufacturer / Supplier

Nova Pressroom Products 1663 North McDuff Avenue Jacksonville, FL 32254

Customer Service: (904) 292-2554 **Transportation:** (800) 424-9300

Fax: (904) 389-6999

E-Mail: info@novapressroom.com

2. Hazard identification

Classification of the substance or mixture

Health hazards:

Acute Toxicity (Oral), Category 5 Skin Irritation, Category 3 Eye Irritation, Category 2B Target Organ Toxicity (Single exposure), Category 3 Aspiration Hazard, Category 1

Physical hazards:

Flammable Liquids, Category 2

Label elements

Highly Flammable Liquid and Vapor



Flame



Exclamation mark



Health hazard

Signal word: DANGER Hazard statement(s)

H225: Highly flammable liquid and vapour.

H303: May be harmful if swallowed.

H316: Causes mild skin irritation.

H320: Causes eye irritation.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

Precautionary statement(s)

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241: Use explosion-proof electrical equipment.

P242: Use non-sparking tools.

P243: Take action to prevent static discharges.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P264: Wash hands thoroughly after handling.

Response:

P301+P312: IF SWALLOWED: Call a POISON CENTER/ doctor/...if you feel unwell.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378: In case of fire: Use dry chemical for extinction.

P312: Call a POISON CENTER or a doctor if you feel unwell.

P331: Do NOT induce vomiting.

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

Storage:

P403+P235: Store in a well-ventilated place. Keep cool.

P233: Keep container tightly closed.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local regulations.

Emergency overview

Physical appearance: Clear, colorless liquid with mild solvent odor.

Immediate concerns: Can cause eye, skin or respiratory tract irritation. Can cause severe lung damage and may be fatal if swallowed. May cause CNS depression. Extremely flammable liquid and vapor. May cause flash fire. Vapors are heavier than air and may travel across the ground and reach remote ignition sources causing a flashback fire. During emergencies, wear equipment to protect eyes, skin and respiratory tract. Dike or absort spills to keep material and run-off from entering sewers, drains or waterways.

Potential health effects

Eye: Contact may cause eye irritation.

Skin: Prolonged or repeated contact with liquid can cause defatting and drying of the skin, and can lead to irritation and/or dermatitis.

Skin absorption: May be harmful if absrobed through skin.

Ingestion: May cause nausea, vomitting, diarrhea; possible chemical pneumonitis if aspirated into lungs.

Inhalation: Irritating to the respiratory tract. May cause headache, dizziness, anesthetic effects (CNS depression). Breathing high concentrations in an enclosed space or by intentional abuse can cause irregular heartbeats, which can cause death.

Medical conditions aggravated: Significant chronic exposure may aggravate existing eye, skin, auditory (hearing), respiratory system, liver, kidney, and CNS conditions.

3. Composition/information on ingredients

Chemical name	% w/w	CAS No.
Low Boiling Point Naphtha - Solvent Naphtha (petroleum), Light Aliph.	70 - 80	64742-89-8
Acetone	10 - 20	67-64-1
2-propanol	5 - 15	67-63-0

4. First-aid measures

Eye: Immediately flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin: Remove contaminated clothing; launder before re-use. Wash skin with soap and water. If irritation develops or persists, seek medical attention.

Ingestion: Seek immediate medical advice. Do NOT induce vomiting, do NOT drink water.

Inhalation: Remove person to fresh air. If breathing becomes difficult, seek medical attention.

5. Fire-fighting measures

Flammable class: Category 2 - Highly Flammable Liquid and Vapor

Suitable extinguishing media: Foam, dry chemical; use water spray to cool exposed surfaces. OSHA Class IB Flammable Liquid. Evacuate area and fight fire from a safe distance if fire is contained in a small area; otherwise, call the local fire department. Fire media runoff may damage the environment. Dike and collect media used to fight fire.

Other considerations: Vapors are heavier than air and may accumulate in low or inadequately ventilated areas. Vapors may travel along the ground to be ignited at locations distant from the handling site. Flashback or flame to the handling site may occur.

Hazardous decomposition products: Fire may produce hazardous fumes.

6. Accidental release measures

Small spill: Wear protective gloves and eye protection, and stop the source of the leak or spill if possible. Isolate area of spill with dike, and/or add dry absorbent to prevent runoff from entering storm sewers and ditches which lead to waterways. Clean up and place in an appropriate container for disposal. Wash all contaminated clothing before use.

Large spill: Follow OSHA emergency response regulations and NIOSH recommendations. If possible, stop source of spill or release. Isolate the area of spill or release with dike to prevent runoff from entering storm sewers and ditches which lead to waterways. Clean up and place in an appropriate container for disposal. Wash all contaminated clothing before use.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes, skin, or clothing. Avoid breathing mist or vapor. Do not swallow. Wash hands thoroughly after handling. Do not eat, drink, or smoke in work areas. Use only with adequate ventilation. Avoid using in areas with open flames, welding arcs, extreme heat or sparks.

Conditions for safe storage: Store in a cool, dry, well-ventilated area. Keep container closed when not in use. Transfer to bonded and grounded containers only. Avoid storage with acids/bases and strong oxidizers. Containers of this material may be hazardous when emptied. Because emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this data sheet must be observed.

8. Exposure controls/personal protection

Exposure controls

Control parameters				
	Occupational exposure limit values			
Chemical name	Туре		ppm	mg/m³
	OSHA PEL	TWA	1000	2400
Acetone	ACGIH TLV	TWA	500	
	ACGIN 1LV	STEL	750	
2-propanol	OSHA PEL	TWA	400	980
	USHA PEL	STEL	500	
	ACGIH TLV	TWA	200	490
	ACGIN ILV	STEL	400	960

Appropriate engineering controls: Good, general ventilation should be sufficient for most operations. Ten or more room air changes per hour containing a minimum of 15% fresh air is recommended.

Individual protection measures, such as personal protective equipment

Eye / face protection: Safety glasses.

Skin protection - hand protection: Gloves impervious to the hazardous ingredients.

Respiratory protection: If used under normal operating conditions and with adequate ventilation, respiratory equipment is not required.

9. Physical and chemical properties

Physical state: Liquid Appearance: Clear

Color: None

Odor: Mild solvent odor

Odor threshold: Not Established

pH: NA = Not Applicable

Freezing point: Not Established

Initial boiling point and boiling range: (133°F) to (285°F)

Flash point: ~ (10°F) TCC

Evaporation rate (n-butyl acetate = 1): Not Established

Lower explosion limit / flammability limit: Not established

Vapor pressure: 8.2 mmHg at 20°C Relative vapor density: Not Established

Density: Not Established

Relative density: 0.72 at (77°F)

Notes: Water = 1.00 Solubility: Insoluble

Partition coefficient n-octanol/water (logarithmic value): Not Established

Auto-ignition temperature: Not Established

Viscosity: Not Established

VOC content: 5.25 lbs/gal USEPA Method 24

10. Stability and reactivity

Dangerous polymerization: No **Chemical stability:** Chemically stable

Conditions to avoid: High temperatures, localized heat sources (i.e.: drum or band heaters), oxidizing conditions, freezing conditions, direct sunlight, ultraviolet radiation, inert gas blanketing, strong oxidizers, strong reducers, free radical initiators, inert gases, oxygen scavengers.

Hazardous decomposition products: Includes, but not limited to smoke, fumes, oxides of nitrogen, and oxides of carbon.

Incompatible materials: Strong oxidizers, acids, and/or bases.

11. Toxicological information

Acute toxicity

Chemical name	LD ₅₀ (oral) mg/kg(rat)	LD ₅₀ (dermal) mg/kg(rabbit)	LC ₅₀ (inhalation) mg/l
Acetone	5800 mg/kg [Rat]	20000 mg/kg [Rabbit]	71 mg/L/4h [Rat]
2-propanol	4700 mg/kg [Rat]	12870 mg/kg [Rabbit]	19000 ppm [Rat]

Acute oral toxicity LD₅₀: Not Established

Specific Target Organ Toxicity - single exposure: May cause drowsiness or dizzyness.

Aspiration hazard: May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicological information: Not Available
Persistence and degradability: Not Available
Bioaccumulative potential: Not Available

13. Disposal considerations

Disposal methods: Dispose materials associated with cleaning spills and/or leaks according to federal, state, and local regulations. If

product is contaminated with other printing process products, consult appropriate federal, state, and local regulations to determine proper characterization of resultant mixture.

RCRA/EPA waste information: D001 (Ignitable Characteristic)

14. Transport information

USA Department of Transport Regulations (DOT)

UN proper shipping name: Flammable liquid, N.O.S. (Petroleum distillates, Acetone)

UN number: 1993

Transport hazard class(es): 3
Packing group, if applicable: ||

NAERG: 128

ICAO - air

UN proper shipping name: None

IMDG - sea

UN proper shipping name: Flammable liquid, N.O.S. (Petroleum distillates, Acetone)

UN number: 1993

Transport hazard class(es): 3
Packing group, if applicable: ||

EmS: F-E, S-E

15. Regulatory information

UNITED STATES

SARA Section 311/312 Hazard Categories

313 reportable ingredients: This product does not contain any ingredients subject to the reporting requirements of SARA Title III Section 313 at or above reporting thresholds, unless listed below.

EPCRA Section 313 Toxic Chemicals

Chemical name	% w/w	CAS N o.
2-propanol	5 - 15	67-63-0

CERCLA Hazardous Substances and Reportable Quantities (RQ)

Chemical name	% w/w	CERCLA rq
Acetone	10 - 20	5,000

TSCA (The Toxic Substances Control Act)

TSCA Status: All components of this product are registered on the TSCA inventory.

CANADA

WHMIS Regulatory Status: Class D2B Toxic Material WHMIS Classification: Class B Flammable Material

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL): All components of this product are registered on the DSL inventory.


16. Other information

Approved by: DB **Title:** Technical Manager **Prepared by:** DB **Date revised:** 10/10/2023

Revision summary: This SDS replaces the 10/10/2023 SDS. Revised: Section 1: Approved by, Prepared by, Title. Section 2:

Classification of the substance or mixture, Label elements, Precautionary statement(s).

HMIS rating Health 2 Flammability 3 Physical hazard 0 Personal protection B



Manufacturer disclaimer:

The specific chemical identities of some ingredients in this mixture are considered proprietary information and trade secrets. As such they are witheld in accordance with CFR 1910.1200(i) of Title 29.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. Some information may be based on indirect test data.