# SAFETY DATA SHEET



Date Prepared : 12/12/2014 SDS No : N-220 Date Revised : 04/17/2018 Revision No: 3

## pressroom products

#### 1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: Premium, Water-Miscible One-Step Roller and Blanket Wash PRODUCT CODE: N-220

#### MANUFACTURER

Nova Pressroom Products 1663 North McDuff Avenue Jacksonville, FL 32254 Alternate Contact: (866) 443-5811 Customer Service: (904) 292-2554 Transportation: (800) 424-9300 Fax: 904) 389-6999 E-Mail: info@novapressroom.com

### 24 HR. EMERGENCY TELEPHONE NUMBERS Chemtrec (US and Canada) : +1-800-424-9300

#### 2. HAZARDS IDENTIFICATION

#### GHS CLASSIFICATIONS

#### Health:

Skin Irritation, Category 3 Eye Irritation, Category 2B Target Organ Toxicity (Single exposure), Category 3 Aspiration Hazard, Category 1

#### Physical:

Flammable Liquids, Category 3

#### GHS LABEL

Flammable Liquid and Vapor



#### SIGNAL WORD: DANGER

#### HAZARD STATEMENTS

H226: Flammable liquid and vapour.

- H316: Causes mild skin irritation.
- H320: Causes eye irritation.
- H304: May be fatal if swallowed and enters airways.
- H336: May cause drowsiness or dizziness.
- H335: May cause respiratory irritation.

#### PRECAUTIONARY STATEMENTS

#### Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

P241: Use explosion-proof electrical equipment.

P242: Use non-sparking tools.

P243: Take action to prevent static discharges.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P264: Wash hands thoroughly after handling.

#### Response:

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P370+P378: In case of fire: Use dry chemical for extinction.

P312: Call a POISON CENTER or a doctor if you feel unwell.

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331: Do NOT induce vomiting.

#### Storage:

P403+P235: Store in a well-ventilated place. Keep cool.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

#### Disposal:

P501: Dispose of contents/container in accordance with local regulations.

#### EMERGENCY OVERVIEW

**PHYSICAL APPEARANCE:** Clear, blue liquid with medium sweet/mild solvent odor.

**IMMEDIATE CONCERNS:** Can cause eye, skin or respiratory tract irritation. Can cause severe lung damage and may be fatal if swallowed. May cause CNS depression. Combustible. Vapors are heavier than air and may travel across the ground and reach remote ignition sources causing a flashback fire. During emergencies, wear equipment to protect eyes, skin and respiratory tract. Dike or absorb spills to keep material and run-off from entering sewers, drains or waterways.

#### POTENTIAL HEALTH EFFECTS

**EYES:** Contact may cause eye irritation.

SKIN: Prolonged or repeated contact with liquid can cause defatting and drying of the skin, and can lead to irritation and/or dermatitis.

SKIN ABSORPTION: May be absorbed through intact skin; however, single, prolonged exposure is not likely to result in the material being absorbed through the skin in harmful amounts.

**INGESTION:** May cause nausea, vomitting, diarrhea; possible chemical pneumonitis if aspirated into lungs.

**INHALATION:** Irritating to the respiratory tract. May cause headache, dizziness, anesthetic effects (CNS depression). Breathing high concentrations in an enclosed space or by intentional abuse can cause irregular heartbeats, which can cause death.

**MEDICAL CONDITIONS AGGRAVATED:** Significant chronic esposure may aggravate existing eye, skin, auditory (hearing), respiratory system, liver, kidney, and CNS conditions.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name		CAS
Aliphatic Petrolleum Distillates	44 - 55	64742-48-9
1,2,4-trimethylbenzene	~ 30	95-63-6
Steareth - 50	< 5	68439-49-6
Cumene	< 1	98-82-8
Xylenes (o-,m-,p- Isomers)	< 1	1330-20-7

#### 4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. If irritation persists, seek medical attention.

**SKIN:** Remove contaminated clothing; launder before re-use. Wash skin with soap and water. If irritation develops or persists, seek medical attention.

**INGESTION:** Seek immediate medical advice. Do NOT induce vomiting, do NOT drink water.

**INHALATION:** Remove person to fresh air. If breathing becomes difficult, seek medical attention.

#### 5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Category 3 - Flammable Liquid and Vapor

**EXTINGUISHING MEDIA:** Foam, dry chemical; use water spray to cool exposed surfaces. Evacuate area and fight fire from a safe distance if fire is contained in a small area; otherwise, call the local fire department. Fire media runoff may damage the environment. Dike and collect media used to fight fire.

**OTHER CONSIDERATIONS:** Vapors are heavier than air and may accumulate in low or inadequately ventilated areas. Vapors may travel along the ground to be ignited at locations distant from the handling site. Flashback or flame to the handling site may occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Fire may produce hazardous fumes.

#### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Wear protective gloves and eye protection, and stop the source of the leak or spill if possible. Isolate area of spill with dike, and/or add dry absorbent to prevent runoff from entering storm sewers and ditches which lead to waterways. Clean up and place in an appropriate container for disposal. Wash all contaminated clothing before use.

LARGE SPILL: Follow OSHA emergency response regulations and NIOSH recommendations. If possible, stop source of spill or release. Isolate the area of spill or release with dike to prevent runoff from entering storm sewers and ditches which lead to waterways. Clean up and place in an appropriate container for disposal. Wash all contaminated clothing before use.

#### 7. HANDLING AND STORAGE

**HANDLING:** Avoid contact with eyes, skin, or clothing. Avoid breathing mist or vapor. Do not swallow. Wash hands thoroughly after handling. Do not eat, drink, or smoke in work areas. Use only with adequate ventilation. Avoid using in areas with open flames, welding arcs, extreme heat or sparks.

**STORAGE:** Store in a cool, dry, well-ventilated area. Keep container closed when not in use. Transfer to bonded and grounded containers only. Avoid storage with acids/bases and strong oxidizers. Containers of this material may be hazardous when emptied. Because emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this data sheet must be observed.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
	EXPOSURE LIMITS			
Chemical Name	Туре		ppm	mg/m³
	OSHA PEL	TWA	500	
Aliphatic Petrolleum Distillates	ACGIH TLV	TWA	100	
1,2,4-trimethylbenzene	ACGIH TLV	TWA	25	123

**ENGINEERING CONTROLS:** Good, general ventilation should be sufficient for most operations. Ten or more room air changes per hour containing a minimum of 15% fresh air is recommended.

#### PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety glasses.

SKIN: Gloves impervious to the hazardous ingredients.

**RESPIRATORY:** If used under normal operating conditions and with adequate ventilation, respiratory equipment is not required.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid **ODOR:** Medium sweet/mild solvent odor **ODOR THRESHOLD:** Not Established **APPEARANCE:** Clear COLOR: Blue pH: NA = Not Applicable FLASH POINT AND METHOD: ~ (107°F) CC FLAMMABLE LIMITS: Not established AUTOIGNITION TEMPERATURE: Not Established VAPOR PRESSURE: 2.1 mmHg at 20°C VAPOR DENSITY: Not Established BOILING POINT: (310°F) to (392°F) FREEZING POINT: Not Established SOLUBILITY IN WATER: 100% Miscible PARTITION COEFFICIENT: N-OCTANOL/WATER: Not Established EVAPORATION RATE: Not Established **DENSITY:** Not Established SPECIFIC GRAVITY: 0.823 at (77°F) Notes: Water = 1.00

VISCOSITY: Not Established

(VOC): 6.67 lbs/gal USEPA Method 24

#### **10. STABILITY AND REACTIVITY**

#### HAZARDOUS POLYMERIZATION: No

**STABILITY:** Chemically stable

**CONDITIONS TO AVOID:** High temperatures, localized heat sources (i.e.: drum or band heaters), oxidizing conditions, freezing conditions, direct sunlight, ultraviolet radiation, inert gas blanketing, strong oxidizers, strong reducers, free radical initiators, inert gases, oxygen scavengers.

HAZARDOUS DECOMPOSITION PRODUCTS: Includes, but not limited to smoke, fumes, oxides of nitrogen, and oxides of carbon.

**INCOMPATIBLE MATERIALS:** Strong oxidizers, acids, and/or bases.

#### 11. TOXICOLOGICAL INFORMATION

#### ACUTE TOXICITY

Chemical Name	ORAL LD <sub>50</sub>	DERMAL LD <sub>50</sub>		
Aliphatic Petrolleum Distillates	5000	3160		

ORAL LD<sub>50</sub>: Not Established

**STOT-SINGLE EXPOSURE:** May cause drowsiness or dizzyness.

ASPIRATION HAZARD: May be fatal if swallowed and enters airways.

#### 12. ECOLOGICAL INFORMATION

#### ECOTOXICOLOGICAL INFORMATION: Not Available

BIOACCUMULATION/ACCUMULATION: Not Available

#### **13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** Dispose materials associated with cleaning spills and/or leaks according to federal, state, and local regulations. If product is contaminated with other printing process products, consult appropriate federal, state, and local regulations to determine proper characterization of resultant mixture.

RCRA/EPA WASTE INFORMATION: D001 (Ignitable Characteristic)

#### 14. TRANSPORT INFORMATION

#### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Combustible liquid, N.O.S. (Petroleum distillates)

**UN/NA NUMBER:** 1993

PACKING GROUP: III

**NAERG:** 128

OTHER SHIPPING INFORMATION: for bulk shipments (>119 gallons); less than bulk quantities are not regulated.

#### AIR (ICAO/IATA)

SHIPPING NAME: Not Available

#### VESSEL (IMO/IMDG)

SHIPPING NAME: Not Available

#### 15. REGULATORY INFORMATION

#### UNITED STATES

#### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**313 REPORTABLE INGREDIENTS:** This product does not contain any ingredients subject to the reporting requirements of SARA Title III Section 313 at or above reporting thresholds, unless listed below.

#### **EPCRA SECTION 313 SUPPLIER NOTIFICATION**

Ch	emical Name	Wt.%	CAS
1,2	2,4-trimethylbenzene	~ 30	95-63-6

#### CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	•	Wt.%	CERCLA RQ
Cumene		< 1	5,000
Xylenes (o-,m-,p	- Isomers)	< 1	100

#### TSCA (TOXIC SUBSTANCE CONTROL ACT)

**TSCA STATUS:** All components of this product are registered on the TSCA inventory.

#### CLEAN AIR ACT

Chemical Name	Wt.%	CAS
Xylenes (o-,m-,p- Isomers)	< 1	1330-20-7

# **40 CFR PART 68--- RISK MANAGEMENT FOR CHEMICAL ACCIDENT RELEASE PREVENTION:** Cumene (<1%); Xylene (<1%)

#### CANADA


#### WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): Class D2B Toxic Material


**DOMESTIC SUBSTANCE LIST (INVENTORY):** All components of this product are registered on the DSL inventory.

#### 16. OTHER INFORMATION

#### **PREPARED BY:** Richard Alan Day - EHS Manager **Date Revised:** 04/17/2018

**REVISION SUMMARY:** This SDS replaces the 03/05/2018 SDS. Revised: **Section 11:** IARC, NTP, OSHA, CARCINOGENICITY. **Section 16:** HMIS RATING - CHRONIC.





#### MANUFACTURER DISCLAIMER:

The specific chemical identities of some ingredients in this mixture are considered proprietary information and trade secrets. As such they are witheld in accordance with CFR 1910.1200(i) of Title 29.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. Some information may be based on indirect test data.