SAFETY DATA SHEET



Date Issued: 01/24/2018

SDS No: NC-7102 Date Revised: 04/29/2021

Revision No: 4

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: UV Matte Coating

PRODUCT CODE: NC-7102

MANUFACTURER

Nova Pressroom Products 1663 North McDuff Avenue Jacksonville, FL 32254

Alternate Contact: (866) 443-5811 Customer Service: (904) 292-2554 **Transportation:** (800) 424-9300

Fax: 904) 389-6999

E-Mail: info@novapressroom.com

24 HR. EMERGENCY TELEPHONE NUMBERS

Chemtrec (US and Canada): +1-800-424-9300

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Eye Corrosion, Category 1 Skin Irritation, Category 2 Skin Sensitization, Category 1 Target Organ Toxicity (Single exposure), Category 3 Reproductive Toxicity, Category 2 Carcinogenicity, Category 2

Environmental:

Acute Hazards to the Aquatic Environment, Category 3 Chronic Hazards to the Aquatic Environment, Category 3

GHS LABEL



Exclamation mark



Corrosion



Health hazard

SIGNAL WORD: DANGER HAZARD STATEMENTS

H318: Causes serious eye damage.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H335: May cause respiratory irritation.

H361: Suspected of damaging fertility or the unborn child

H351: Suspected of causing cancer

H412: Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed out of the workplace.

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P273: Avoid release to the environment.

P261: Avoid breathing dust, vapours or spray.

Response:

P312: Call a POISON CENTER or a doctor if you feel unwell.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: IF IN EYES: Immediately call a POISON CENTER or doctor.

P302+P352: IF ON SKIN: Wash with plenty of water.

P321: Specific treatment (See First Aid Section on this label).

P308+P313: IF exposed or concerned: Get medical advice/ attention.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P314: Get medical advice/attention if you feel unwell.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

P235+P410: Keep cool. Protect from sunlight.

Disposal:

P501: Dispose of contents/container in accordance with local regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Clear liquid with mild odor

POTENTIAL HEALTH EFFECTS

EYES: Corrosive, contact causes severe eye burns.

SKIN: Irritating to skin. Sensitization may occur.

INGESTION: Ingestion may cause irritation to the gastrointestinal tract. **INHALATION:** Inhalation may cause irritation to the respiratory tract.

MEDICAL CONDITIONS AGGRAVATED: Significant chronic exposure may aggravate existing eye, skin, auditory (hearing), respiratory system, liver, kidney, and CNS conditions.

COMMENTS: Proprietary Acrylated Mixture contributes, but may not be the only ingredient to contribute, and may not be limited to contributing, the following hazards to this product: Eye corrosion catagory 1, Skin irritation catagory 2, Skin sensitizer catagory 1, Specific target organ toxicity catagory 3, Acute hazards to aquatic environments catagory 3, and Chronic hazards to aquatic environments catagory 3.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Proprietary Acrylated Mixture	60 - 80	Mixture
Proprietary - 10326	1 - 10	
Proprietary 10338	1 - 10	
Benzophenone	1 - 5	119-61-9
N-vinyl-2-pyrrolidone	< 1	88-12-0
Proprietary 10428	< 5	

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. If irritation persists, seek medical attention.

SKIN: Wash skin with soap and water. If irritation develops or persists, seek medical attention.

INGESTION: Seek immediate medical advice. Do not induce vomiting unless instructed to do so by poison center or physician.

INHALATION: Remove person to fresh air. If breathing becomes difficult, seek medical attention.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: None

EXTINGUISHING MEDIA: Foam, dry chemical; use water spray to cool exposed surfaces. Evacuate area and fight fire from a safe distance if fire is contained in a small area; otherwise, call the local fire department. Fire media runoff may damage the environment. Dike and collect media used to fight fire.

OTHER CONSIDERATIONS: Vapors are heavier than air and may accumulate in low or inadequately ventilated areas. Vapors may travel along the ground to be ignited at locations distant from the handling site. Flashback or flame to the handling site may occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Fire may produce hazardous fumes.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Wear protective gloves and eye protection, and stop the source of the leak or spill if possible. Isolate area of spill with dike, and/or add dry absorbent to prevent runoff from entering storm sewers and ditches which lead to waterways. Clean up and place in an appropriate container for disposal. Wash all contaminated clothing before use.

LARGE SPILL: Follow OSHA emergency response regulations and NIOSH recommendations. If possible, stop source of spill or release. Isolate the area of spill or release with dike to prevent runoff from entering storm sewers and ditches which lead to waterways. Clean up and place in an appropriate container for disposal. Wash all contaminated clothing before use.

7. HANDLING AND STORAGE

HANDLING: Avoid contact with eyes, skin, or clothing. Avoid breathing mist or vapor. Do not swallow. Wash hands thoroughly after handling. Do not eat, drink, or smoke in work areas. Use only with adequate ventilation. Good housekeeping should be observed to avoid contamination. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used.

STORAGE: Store in a cool, dry, well-ventilated area. Keep container closed when not in use. Keep away from oxidizing agents and corrosives. Protect from direct sunlight and store between 40F and 140F. Containers of this material may be hazardous when emptied. Because emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this data sheet must be observed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
	EXPOSURE LIMITS				
Chemical Name	Туре		ppm	mg/m³	
N-vinyl-2-pyrrolidone	ACGIH TLV	TWA	0.05	0.23	

ENGINEERING CONTROLS: Good, general ventilation should be sufficient for most operations. Ten or more room air changes per hour containing a minimum of 15% fresh air is recommended.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety glasses.

SKIN: Gloves impervious to the hazardous ingredients.

RESPIRATORY: If used under normal operating conditions and with adequate ventilation, respiratory equipment is not required.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Mild odor **APPEARANCE:** Clear

COLOR: None

pH: NA = Not Applicable

FLASH POINT AND METHOD: > (200°F) CC

FLAMMABLE LIMITS: Not Established

AUTOIGNITION TEMPERATURE: Not Established

VAPOR PRESSURE: Not Established
VAPOR DENSITY: Not Established
BOILING POINT: Not Available
FREEZING POINT: Not Established

THERMAL DECOMPOSITION: Not Established

SOLUBILITY IN WATER: Insoluble

PARTITION COEFFICIENT: N-OCTANOL/WATER: Not Established

EVAPORATION RATE: Not Established

DENSITY: Not Established

SPECIFIC GRAVITY: 1.05 to 1.11 at (60°F)

Notes: Water = 1.00

VISCOSITY #1: 140 to 160 cps. at (77°F) #2 @ 60

(VOC): < 0.01 lbs/gal USEPA Method 24

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Uncontrollable polymerization of the product with generation of heat can occur above room temperature or if exposed to direct sunlight.

STABILITY: Chemically stable

CONDITIONS TO AVOID: High temperatures, localized heat sources (i.e.: drum or band heaters), oxidizing conditions, freezing conditions, direct sunlight, ultraviolet radiation, inert gas blanketing, strong oxidizers, strong reducers, free radical initiators, inert gases, oxygen scavengers.

HAZARDOUS DECOMPOSITION PRODUCTS: Includes, but not limited to smoke, fumes, oxides of nitrogen, and oxides of carbon. **INCOMPATIBLE MATERIALS:** Rust, stong oxidizers, acids, and/or bases.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀	INHALATION LC ₅₀
Proprietary - 10326	> 5000 mg/kg [Rat]	> 2000 mg/kg [Rat]	
Proprietary 10338	> 300 to 2000 mg/kg [Rat]		
Benzophenone	2895 mg/kg [Mouse]	3535 mg/kg [Rabbit]	
N-vinyl-2-pyrrolidone	1500 mg/kg [Rat]	560 mg/kg [Rabbit]	3.32 mg/L/4h [Rabbit]
Proprietary 10428	5000 mg/kg [Rat]	> 2000 mg/kg [Rat]	

ORAL LD₅₀: Not Established

CARCINOGENICITY

IARC: Benzophenone <10%: Group 2B (Possibly carcinogenic to humans)

Proprietary 10338 <10%: Group 2B

NOTES: IARC catagory 2B is used for agents for which there is limited evidence of carcinogenicity in humans and less than sufficient evidence of carcinogenicity in experimental animals. It may also be used when there is inadequate evidence of carcinogenicity in humans but there is sufficient evidence of carcinogenicity in experimental animals. In some instances, an agent for which there is inadequate evidence of carcinogenicity in humans and less than sufficient evidence of carcinogenicity in experimental animals together with supporting evidence from mechanistic and other relevant data may be placed in this group. An agent may be classified in this category solely on the basis of evidence from mechanistic and other relevant data.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Not Available

BIOACCUMULATION/ACCUMULATION: Not Available

CHEMICAL FATE INFORMATION: Not Available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose materials associated with cleaning spills and/or leaks according to federal, state, and local regulations. If product is contaminated with other printing process products, consult appropriate federal, state, and local regulations to determine proper characterization of resultant mixture.

RCRA/EPA WASTE INFORMATION: None

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not Regulated

AIR (ICAO/IATA)

SHIPPING NAME: Not Regulated

VESSEL (IMO/IMDG)

SHIPPING NAME: Not Regulated

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

313 REPORTABLE INGREDIENTS: This product does not contain any ingredients subject to the reporting requirements of SARA Title III Section 313 at or above reporting thresholds, unless listed below.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Benzophenone	119-61-9

TSCA STATUS: All components of this product are registered on the TSCA inventory.

CANADA

WHMIS (WORK PLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): Class D2B Toxic Material

DOMESTIC SUBSTANCE LIST (INVENTORY): All components of this product are registered on the DSL inventory.

16. OTHER INFORMATION

APPROVED BY: HRB TITLE: VP Technical Services


PREPARED BY: DCB - EHS Manager Date Revised: 04/29/2021

REVISION SUMMARY: This SDS replaces the 09/11/2019 SDS. Revised: Section 9: SPECIFIC GRAVITY.



HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	В

NFPA CODES



MANUFACTURER DISCLAIMER:

The specific chemical identities of some ingredients in this mixture are considered proprietary information and trade secrets. As such they are witheld in accordance with CFR 1910.1200(i) of Title 29.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. Some information may be based on indirect test data.